

HIPERMAX



LANCER EVOLUTION X



■Features

- HIPERMAX's single tube technology enables comfortable ride even on rough road surfaces.
- With the initial gain characteristic of damping force, handling is smooth.
Damping force of bumping side is less to achieve comfortable ride.
- 30 steps damping force adjustment mechanism enables various settings.
- High durability with stock upper mount and dust boots for both front and rear.

■Parts List

Parts List				
		Front Damper Assy	2	
		Rear Damper Assy	2	
Adjustment Cable		2		2
		2		1
		2		2
		4		2
		1		2
		1		

Damper Components	
FRONT	REAR
<p> Torque Specs: $61 \pm 9 \text{ N}\cdot\text{m}$ Torque Specs: $60 \text{ N}\cdot\text{m}$ </p>	<p> Torque Specs: $25 \pm 5 \text{ N}\cdot\text{m}$ Torque Specs: $40 \text{ N}\cdot\text{m}$ </p>

* Assembled with Damper Assy

Vehicle	Model	Engine	Model Year	Spring rate [N/mm (kgf/mm)]	Spring Height (mm)	Default ride height Range (High-Low)	Code No.	Price
LANCER EVOLUTION X	CZ4A	4B11	07/10-	F=78 (8) R=69 (7)	F=220(Barrel) R=250	F=-38(-28 - -54) R=-16(-3 - -35)	80180-KM001	
Upper Mount	Upper mount change at factory		Spring rate change at factory		Remarks			
F=Stock R=Stock	Not possible		Possible					